



THOMAS MAXWELL

ARTISAN LEATHERS

LANGHAM 5 colours

Thomas Maxwell Leather Quality Guarantee

For a period of three years, for both Domestic and Commercial applications, we guarantee to replace any leather which is found to be faulty as a result of manufacturing defect and which has been used in accordance with our performance ratings and care instructions.

This Guarantee is additional to all statutory rights and remedies that are available to our customers under Consumer Law.

Colour Variations

All leather colours will be supplied within commercial shade tolerances, however some natural colour variations may occur from batch to batch. If colour matching is critical please contact our sales office.

Available from
Warwick Fabrics:

AUSTRALIA

T: 1300 787 888
F: +61 (0) 3 9416 1060
info@warwick.com.au
www.warwick.com.au

NEW ZEALAND

T: +64 (0) 9 477 3080
F: +64 (0) 9 479 6313
info@warwick.co.nz
www.warwick.co.nz

Langham is a full aniline surface grain leather with a wax pull up effect. The hides have been tumbled and infused with oil to give a lovely soft hand. Langham is well suited to both classic and contemporary designs, and is recommended for use in both heavy domestic and general commercial applications.

Specifications	Langham		
Performance	Heavy Domestic & General Commercial		
Warranty	3 Years		
Care	Should include the application of commercially available leather care products, used in accordance with care label instructions.		
Animal Source	Bovine Cattlehide		
Origin	Italian with selected European breed		
Type	Surface grain, lightly buffed, finished with a vintage waxed pull up effect.		
Thickness	0.9 - 1.1mm		
Average Hide Size	5m2		
Rubfastness (grey scale grade)	Marring	Transfer	Results
ISO 11640 Dry 50 Wet 20 Sweat 20	4	3/4	Pass
	4	4	Pass
	4	3/4	Pass
Fastness to Light (Blue wool rating)	3/4		Pass
ISO 105:B02			
Flex Endurance (20,000 flexes)	No Cracks		Pass
ISO 5402			
Tear Strength (N)			
ISO 3377-1 Along Across Average	22		Pass
	31		Pass
	29		Pass
pH ISO 4045:1998	4		Pass
pH difference	-		-
Colourfastness to water (spotting) (grey scale grade)	4 no permanent swelling		Pass
ISO 15700			
Formaldehyde (mg/kg)	< 5		Pass
ISO / TS 17226:2008			
Flammability AS1530.3	Ignitability Index	16	
	Spread of Flame Index	0	
	Heat Evolved Index	2	
	Smoke Developed Index	2	

Please Note: Median test results displayed based off results from light, medium, & dark hides.