



THOMAS MAXWELL

ARTISAN LEATHERS

LONDON CLUB 5 colours

London Club is a surface grain, lightly buffed leather selection, finished with a vintage waxed pull up effect. Its unique antique appearance will be enhanced with age. Recommended for use in both heavy domestic and general commercial applications.

Thomas Maxwell Leather Quality Guarantee

For a period of three years, for both domestic and commercial applications, we guarantee to replace any leather which is found to be faulty as a result of manufacturing defect and which has been used in accordance with our performance ratings and care instructions.

This Guarantee is additional to all statutory rights and remedies that are available to our customers under Consumer Law.

Colour Variations

All leather colours will be supplied within commercial shade tolerances, however some natural colour variations may occur from batch to batch. If colour matching is critical please contact our sales office.

Available from
Warwick Fabrics:

AUSTRALIA
T: 1300 787 888
F: +61 (0) 3 9416 1060
info@warwick.com.au
www.warwick.com.au

NEW ZEALAND
T: +64 (0) 9 477 3080
F: +64 (0) 9 479 6313
info@warwick.co.nz
www.warwick.co.nz

Specifications		London Club		
Performance		Heavy Domestic & General Commercial		
Warranty		3 Years		
Care		Should include the application of commercially available leather care products, used in accordance with care label instructions.		
Animal Source		Bovine Cattlehide		
Origin		Italian with Selected European Breed		
Type		Surface grain, lightly buffed, finished with a vintage waxed pull up effect.		
Thickness		0.9 - 1.1mm		
Average Hide Size		5m2		
Rubfastness (grey scale grade) EN ISO 11640 (SLF450)	Dry 500	Marring	Transfer	Results
	Dry 50	4	4	Pass
	Wet 20	4/5	4/5	Pass
	Sweat 20	4/5	4	Pass
		4/5	3/4	Pass
Fastness to Light (Blue wool rating) EN ISO 105:B02 (SLF 402)		>3		Pass
Finish Adhesion (N/cm) EN ISO 11644 (IUF470)	Along	3.2		Pass
	Across	3.5		Pass
	Average	3.3		Pass
Tear Strength (N) EN ISO 3377-1 (IUP 8)	Along	31		Pass
	Across	35		Pass
	Average	33		Pass
pH EN ISO 4045 (IUC 11)		4		Pass
Water Spotting 10% Alcohol (grey scale grade) EN ISO 15700		4/5		Pass
Formaldehyde ISO 17226-1		14ppm		Pass
Flammability IMO RESOLUTION A.652 (16)		Pass		
Flammability AS1530.3		Ignitability Index 16		
		Spread of Flame Index 0		
		Heat Evolved Index 3		
		Smoke Developed Index 3		

Please Note: Median test results displayed based off results from light, medium, & dark hides.