

LUSTRELL GRID

Specifications

Collection(s)	-
Colour(s)	Bronze, Gold, Gunmetal, Nickel, Onyx, Pearl, Silver
Warwick Brand	Lustrell
Usage	Heavy Commercial
Composition	78% Pvc 20% Polyester 2% Polyurethane
Pattern match	Yes
Pattern repeat (cm)	H: 3 x V: 2
Railroaded	No
Width (cm)	138
Weight (gsm)	625
Origin	Non EU
Stain Repellent	No
FIAA Care Label*	L

*Please refer to Warwick Price List or Website www.warwick.co.nz

Test Results

Abrasion Martindale (ISO 12947, 12kPa)	150,000 Cycles
Seam slippage (mm) (ISO 13936-2, Load 180)	Warp 2.00, Weft 2.00
Pilling resistance (ISO 12945-2)	NA
Colourfastness to light Xenon arc (ISO 105-B02, blue std 6)	>6
Colourfastness to rubbing (ISO 105-X12)	Dry 4, Wet 4
Free and Hydrolysed formaldehyde (ISO 14184-1:1998)	Not Detet cable
Flammability AS/NZS 1530.3-1999	
Ignitability (0 - 20)	11
Spread of flame (0 - 10)	0
Heat evolved (0 - 10)	2
Smoke developed (0 - 10)	6

